

AVK CONTAINERISED GENERATORS

AVK Containerised Generators

AVK/ISO20 Container

The AVK/ISO20 Containers are designed in accordance with dimensions defined by the ISO/TC104 standards. This design enables ease of transport safely, by boat or by road using standard ISO dimensions without specific constraints. Two sizes are available: 20 and 40 feet High Cube.



AVK/ISO20 Container



AVK/EUR40 Container

AVK/EUR40 Container

Dedicated to generating sets equipped with MTU-DDC Series 4000 engines, the EUR 40 Contenergy offers two noise levels on the same base: Silent and Super Silent. This optimised soundproofed version also offers features such as side doors and a day tank.

AVK/CIR20 Container

The AVK/CIR Container is built on an ISO20 Contenergy base. This very compact model is more specifically suited for rental and mobile applications due to its high capacity and its low sound level. Compliance with ISO/TC104 standards are available upon request.



AVK/CIR20 Container



For more information on our full range of Diesel Generators and UPS systems or for a full quotation, please telephone AVK | SEG (UK) LTD on 01628 503900.





AVK CONTAINERISED GENERATORS

Specification

Sound Levels						
Range	Genset Type	Engine	Silent 85-87dB(A)@1m	Silent 84-86dB(A)@1m	Super Silent 78-80dB(A)@1m	Super Silent 82-84dB(A)@1m
Exel	X715K-X800K	12V2000	ISO 20 Si	X	CIR 20 SSI	X
	X910K-X1000K	16V2000	ISO 20 Si	X	CIR 20 SSI	X
	X1100K	18V2000	ISO 20 Si	X	CIR 20 SSI	X
	X1540K-X1700K	12V4000	ISO 40 Si	X	EUR 40 SSI	CIR 20 SSI
	X2000K-X2200K	16V4000	X	EUR 40 Si	EUR 40 SSI	X

Standard & Options		Silent			Super Silent	
		ISO 20 Si	ISO 40 Si	EUR 40 Si	EUR 40 SSI	EUR 40 SSI
Base	Base girder	●	●	●	●	●
	Starter, charging alternator 24V	●	●	●	●	●
	Batteries with electrolyte	SO001	SO001	SO002	SO001	SO001
	Standard air-filter	●	●	●	●	●
	Lube oil drain lamp	●	●	●	●	●
Specifications	Sound-proofing type	Si	Si	Si	SSI	SSI
	Highly efficient silencer built in – attenuation 30dB(A)	●	●	●	●	●
	Floor	Wood	Wood	Wood	Watertight Steel	Wood
	Number of doors	1	1	2	2	2
	Air outlet galvanised steel rain guard grid	CT005	CT005	●	●	●
	Emergency light and emergency fuel valve	CT007	CT007	CT007	CT007	CT007
	Exhaust exit on flanges	CT011	CT011	CT011	CT011	CT011
Fuel	White paint finish (RAL 9010)	●	●	●	●	●
	Bunded floor	CT014	CT014	CT014	CT014	CT014
	Tank without retention bund 500 L	●	X	X	●	X
	Tank with retention bund 500 L	X	●	●	X	●
	Tank with retention bund 2347 L	X	X	X	CT003	X
	Auto Fuel kit (1 pump 1m ³ /H)	CT008	CT008	CT008	CT008	CT008
	Auto Fuel kit (2 pump 1m ³ /H)	X	CT009	CT009	X	CT009
Panels	Auto Fuel kit (2 pump 4m ³ /H)	X	CT010	CT010	X	CT010
	Electric panel EC compliance	●	●	●	●	●
	Panel MICS TELYS	CM40	CM40	CM40	CM40	CM40
Dims.	Panel MICS KERYS	CA600	CA600	CA600	CA600	CA600
	Length (mm)	6058	12192	12192	6058	12192
	Width (mm)	2438	2438	2438	2438	4420
	Height (mm)	2896	2896	2896	2896	2591

● Standard X Not permitted CT Option code

AVK|SEG (UK) LTD
Power Systems House, Malvern Road
Maidenhead
Berkshire
SL6 7QY

Telephone: 01628 503900 Fax: 01628 503999
www.avk-seg.co.uk email: powersystems@avk-seg.co.uk