



#### DESCRIPTIVE

- Electronic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for core temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts (CE option)
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 24 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

#### POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

#### TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

#### ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

## V650C2

Engine ref.	TAD1642GE
Alternator ref.	KH02880T
Performance class	G3

#### GENERAL CHARACTERISTICS

Frequency (Hz)	50 Hz
Voltage (V)	400/230
Standard Control Panel	APM403
Optional control panel	APM802
Optional Control Panel	M80
Optional control panel	TELYS

#### POWER

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
415/240	520	650	473	591	904
400/230	520	650	473	591	938
380/220	520	650	473	591	988
200/115	520	650	473	591	1876
240 TRI	520	650	473	591	1564
230 TRI	520	650	473	591	1632
220 TRI	520	650	473	591	1706

#### DIMENSIONS COMPACT VERSION

Length (mm)	3470
Width (mm)	1630
Height (mm)	2095
Dry weight (kg)	3780
Tank capacity (L)	610

#### DIMENSIONS SOUNDPROOFED VERSION

Type soundproofing	M230
Length (mm)	5031
Width (mm)	1690
Height (mm)	2672
Dry weight (kg)	5300
Tank capacity (L)	610
Acoustic pressure level @1m in dB(A)	80
Sound power level guaranteed (Lwa)	100
Acoustic pressure level @7m in dB(A)	70



## V650C2

### ENGINE CHARACTERISTICS

#### GENERAL ENGINE DATA

Engine brand	VOLVO
Engine ref.	TAD1642GE
Air inlet system	Turbo
Cylinders configuration	L
Number of cylinders	6
Displacement (L)	16,12
Charge Air coolant	Air/Air DC
Bore (mm) x Stroke (mm)	144 x 165
Compression ratio	16.5 : 1
Speed (RPM)	1500
Pistons speed (m/s)	8,25
Maximum stand-by power at rated RPM (kW)	565
Frequency regulation, steady state (%) +/- 0.5%	
BMEP (bar)	25,50
Governor type	Electronic

#### COOLING SYSTEM

Radiator & Engine capacity (L)	60
Fan power (kW)	11
Fan air flow w/o restriction (m3/s)	10
Available restriction on air flow (mm H2O)	30
Type of coolant	Glycol-Ethylene

#### EMISSIONS

Emission PM (g/kW.h)	0,11
Emission CO (g/kW.h)	0,67
Emission HC+NOx (g/kWh)	5,67
Emission HC (mg/Nm3) 5% O2	

#### EXHAUST

Exhaust gas temperature @ ESP 50Hz (°C)	482
Exhaust gas flow @ ESP 50 Hz (L/s)	1708
Max. exhaust back pressure (mm H2O)	1000

#### FUEL

Consumption @ 110% load (L/h)	132,90
Consumption @ 100% load (L/h)	119,60
Consumption @ 75% load (L/h)	88,40
Consumption @ 50% load (L/h)	58,90
Maximum fuel pump flow (L/h)	180

#### OIL

Oil capacity (L)	48
Min. oil pressure (bar)	0,70
Max. oil pressure (bar)	6,50
Oil consumption 100% ESP (L/h)	0,70
Oil sump capacity (L)	42

#### HEAT BALANCE

Heat rejection to exhaust (kW)	427
Radiated heat to ambient (kW)	20
Heat rejection to coolant HT (kW)	218

#### AIR INTAKE

Max. intake restriction (mm H2O)	500
Intake air flow (L/s)	676



# V650C2

## ALTERNATOR CHARACTERISTICS

### GENERAL DATA

Alternator ref.	KH02880T
Number of Phase	Three phase
Power factor (Cos Phi)	0,80
Altitude (m)	0 à 1000
Overspeed (rpm)	2250
Number of pole	4
Capacity for maintaining short circuit at 3 In for 10 s	No
Insulation class	H
T° class (H/125°), continuous 40°C	H / 125°K
T° class (H/163°C), standby 27°C	H / 163°K
Total Harmonic Distortion in no-load DHT (%)	<2
AVR Regulation	Yes
Total Harmonic Distortion, on linear load DHT (%)	<2
Wave form : NEMA=TIF	<50
Wave form : CEI=FHT	<2
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (+/- %)	0,50
Recovery time (Delta U = 20% transient) (ms)	500
Indication of protection	IP 23
Technology	Without collar or brush

### OTHER DATA

Continuous Nominal Rating 40°C (kVA)	600
Standby Rating 27°C (kVA)	660
Efficiencies 100% of load (%)	94,50
Air flow (m3/s)	0,90
Short circuit ratio (Kcc)	0,3650
Direct axis synchro reactance unsaturated (Xd) (%)	330
Quadra axis synchro reactance unsaturated (Xq) (%)	168
Open circuit time constant (T'do) (ms)	1997
Direct axis transient reactance saturated (X'd) (%)	16,50
Short circuit transient time constant (T'd) (ms)	100
Direct axis subtransient reactance saturated (X''d) (%)	11,50
Subtransient time constant (T''d) (ms)	10
Quadra axis subtransient reactance saturated (X''q) (%)	15,20
Subtransient time constant (T''q) (ms)	10
Zero sequence reactance unsaturated (Xo) (%)	0,60
Negative sequence reactance saturated (X2) (%)	13,43
Armature time constant (Ta) (ms)	15
No load excitation current (io) (A)	0,92
Full load excitation current (ic) (A)	3,65
Full load excitation voltage (uc) (V)	62,10
Engine start (Delta U = 20% perm. or 30% trans.) (kVA)	1144,84
Transient dip (4/4 load) - PF : 0,8 AR (%)	15
No load losses (W)	6794,24
Heat rejection (W)	27572,30
Unbalanced load acceptance ratio (%)	70

## DIMENSIONS

### Dimensions soundproofed version

Type soundproofing	M230
Length (mm)	5031
Width (mm)	1690
Height (mm)	2672
Dry weight (kg)	5300
Tank capacity (L)	610
Acoustic pressure level @1m in dB(A)	80
Sound power level guaranteed (Lwa)	100
Acoustic pressure level @7m in dB(A)	70

### Dimensions DW soundproofed version

Type soundproofing	M230 DW
Length (mm)	5083
Width (mm)	1690
Height (mm)	2932
Dry weight (kg)	5910
Tank capacity (L)	1950


### Dimensions DW compact version

Type soundproofing	
Length (mm)	5083
Width (mm)	1960
Height (mm)	2355
Dry weight (kg)	4420
Tank capacity (L)	1950
Acoustic pressure level @1m in dB(A)	
Sound power level guaranteed (Lwa)	
Acoustic pressure level @7m in dB(A)	

Acoustic pressure level @ 1m in dB(A)	80
Sound power level guaranteed (Lwa)	100
Acoustic pressure level @ 7m in dB(A)	70



### APM403, basic generating set and power plant control



The APM403 is a versatile control unit which allows operation in manual or automatic mode  
Measurements : voltage and current  
kW/kWh/kVA power meters  
Standard specifications: Voltmeter, Frequency meter.  
Optional : Battery ammeter.  
J1939 CAN ECU engine control  
Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.  
Engine parameters: Fuel level, hour counter, battery voltage.  
Optional (standard at 24V): Oil pressure, water temperature.  
Event log/ Management of the last 300 genset events.  
Mains and genset protection  
Clock management  
USB connections, USB Host and PC,  
Communications : RS485 INTERFACE  
ModBUS protocol /SNMP  
Optional : Ethernet, GPRS, remote control, 3G, 4G,  
Websupervisor, SMS, E-mails

### APM802 dedicated to power plant management



The new APM802 command/control system is specifically designed for operating and monitoring power plants for markets including hospitals, data centres, banks, the oil and gas sector, industries, IPP, rental and mining.  
This unit is available as standard on all generating sets from 275 Kva designed for coupling. It is optional on the rest of our range.  
The Human Machine Interface, designed in collaboration with a company specialising in interface design, facilitates operations with a large 100% touch screen. The pre-configured system for power plant applications features a brand new customisation function which complies with the international standard IEC 61131-3. New communication functions (PLC and regulation), improve the high level of equipment availability in the installation.

Advantages:  
Dedicated to power plant management.  
Specially researched ergonomics.  
High level of equipment availability.  
Modularity and long service life guaranteed.  
Making it easy to extend the installation

For more information, please refer to the sales documentation.

## M80, transfer of information



The M80 is a dual-function control unit. It can be used as a basic terminal block for connecting a control box and as an instrument panel with a direct read facility, with displays giving a global view of your generating set's basic parameters.

Offers the following functions:

Engine parameters: tachometer, working hours counter, coolant temperature indicator, oil pressure indicator, emergency stop button, customer connection terminal block, CE.

## TELYS, ergonomic and user-friendly



The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

Ergonomics: wheel for navigating around the various menus.

Communication: remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.